




# HYDRA HOT



### WORKING CONDITIONS

Max working pressure \_\_\_\_\_ 8 bar (116 psi)  
 Min working pressure \_\_\_\_\_ 1,8 bar (26 psi)  
 Max working temperature \_\_\_\_\_ 80°C (176°F)  
 Min working temperature \_\_\_\_\_ 4°C (39,2°F)

### SPECIFICATIONS

Non-toxic materials.  
 Head: reinforced nylon.  
 Bowl: reinforced nylon.  
 O-ring: EPDM.  
 Breather-valve: body stainless steel, o-ring EPDM.  
 Discharge ball-valve: CW 617 N brass nickel plated.  
 Discharge plastic nipple: reinforced polypropylene.  
 Drain funnel: reinforced polypropylene.



**DRAIN FUNNEL**  
 Back-flow preventing device  
 UNI EN 1717-11/2002

## HYDRA HOT single-stage self-cleaning filters

### HOUSINGS WITH PLASTIC BSP THREADS

CODE	MODEL	NOMINAL FILTRATION MICRON	IN/OUT	THREADS	FLOW RATE l/h	DIMENSIONS mm		
						A	B	C
RA6000001	HYDRA HOT 1/2" RAH 90 mcr IN	90	1/2"	PLASTIC-BSP	3500	390	120	107
RA6000002	HYDRA HOT 3/4" RAH 90 mcr IN	90	3/4"	PLASTIC-BSP	5000	390	120	107
RA6000003	HYDRA HOT 1" RAH 90 mcr IN	90	1"	PLASTIC-BSP	6000	390	120	107

### HOUSINGS WITH PLASTIC NPT THREADS

CODE	MODEL	NOMINAL FILTRATION MICRON	IN/OUT	THREADS	FLOW RATE l/h	DIMENSIONS mm		
						A	B	C
RA6000005	HYDRA HOT 3/4" RAH 90 mcr NPT IN	90	3/4"	PLASTIC-NPT	5000	390	120	107
RA6000006	HYDRA HOT 1" RAH 90 mcr NPT IN	90	1"	PLASTIC-NPT	6000	390	120	107

www.VodnneFiltere.sk