




PLUS 3P SX SANIC

WORKING CONDITIONS

Max working pressure _____ 8 bar (116 psi)
 Max working temperature _____ 45°C (113°F)
 Min working temperature _____ 4°C (39,2°F)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head and ring nut: reinforced polypropylene.
 Bowl: PET with antimicrobial technology.
 O-ring: EPDM.
 Breather-valve: body polypropylene, o-ring EPDM.
 IN/OUT brass threads: CW 614 N brass.



PLUS 3P SX SANIC

HOUSINGS WITH BRASS BSP THREADS

| CODE | MODEL | SUITABLE CARTRIDGE | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|-----------------------------|--------------------|--------|-----------|---------------|-----|-----|
| | | | | | A | B | C |
| SA107T111 | MEDIUM PLUS 3P MFO SX SANIC | 5" | 1/2" | BRASS-BSP | 191 | 133 | 130 |
| SA107T411 | MEDIUM PLUS 3P AFO SX SANIC | 5" | 3/4" | BRASS-BSP | 191 | 133 | 130 |
| SA107T711 | MEDIUM PLUS 3P BFO SX SANIC | 5" | 1" | BRASS-BSP | 197 | 145 | 130 |
| SA109T111 | JUNIOR PLUS 3P MFO SX SANIC | 7" | 1/2" | BRASS-BSP | 241 | 133 | 130 |
| SA109T411 | JUNIOR PLUS 3P AFO SX SANIC | 7" | 3/4" | BRASS-BSP | 241 | 133 | 130 |
| SA109T711 | JUNIOR PLUS 3P BFO SX SANIC | 7" | 1" | BRASS-BSP | 247 | 145 | 130 |
| SA111T111 | SENIOR PLUS 3P MFO SX SANIC | 10" | 1/2" | BRASS-BSP | 315 | 133 | 130 |
| SA111T411 | SENIOR PLUS 3P AFO SX SANIC | 10" | 3/4" | BRASS-BSP | 315 | 133 | 130 |
| SA111T711 | SENIOR PLUS 3P BFO SX SANIC | 10" | 1" | BRASS-BSP | 321 | 145 | 130 |
| SA115T111 | MASTER PLUS 3P MFO SX SANIC | 20" | 1/2" | BRASS-BSP | 571 | 133 | 130 |
| SA115T411 | MASTER PLUS 3P AFO SX SANIC | 20" | 3/4" | BRASS-BSP | 571 | 133 | 130 |
| SA115T711 | MASTER PLUS 3P BFO SX SANIC | 20" | 1" | BRASS-BSP | 577 | 145 | 130 |

HOUSINGS WITH PLASTIC BSP THREADS

| CODE | MODEL | SUITABLE CARTRIDGE | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|-----------------------------|--------------------|--------|-------------|---------------|-----|-----|
| | | | | | A | B | C |
| SA107T211 | MEDIUM PLUS 3P MFP SX SANIC | 5" | 1/2" | PLASTIC-BSP | 191 | 133 | 130 |
| SA107T511 | MEDIUM PLUS 3P AFP SX SANIC | 5" | 3/4" | PLASTIC-BSP | 191 | 133 | 130 |
| SA107T811 | MEDIUM PLUS 3P BFP SX SANIC | 5" | 1" | PLASTIC-BSP | 197 | 145 | 130 |
| SA109T211 | JUNIOR PLUS 3P MFP SX SANIC | 7" | 1/2" | PLASTIC-BSP | 241 | 133 | 130 |
| SA109T511 | JUNIOR PLUS 3P AFP SX SANIC | 7" | 3/4" | PLASTIC-BSP | 241 | 133 | 130 |
| SA109T811 | JUNIOR PLUS 3P BFP SX SANIC | 7" | 1" | PLASTIC-BSP | 247 | 145 | 130 |
| SA111T211 | SENIOR PLUS 3P MFP SX SANIC | 10" | 1/2" | PLASTIC-BSP | 315 | 133 | 130 |
| SA111T511 | SENIOR PLUS 3P AFP SX SANIC | 10" | 3/4" | PLASTIC-BSP | 315 | 133 | 130 |
| SA111T811 | SENIOR PLUS 3P BFP SX SANIC | 10" | 1" | PLASTIC-BSP | 321 | 145 | 130 |
| SA115T211 | MASTER PLUS 3P MFP SX SANIC | 20" | 1/2" | PLASTIC-BSP | 571 | 133 | 130 |
| SA115T511 | MASTER PLUS 3P AFP SX SANIC | 20" | 3/4" | PLASTIC-BSP | 571 | 133 | 130 |
| SA115T811 | MASTER PLUS 3P BFP SX SANIC | 20" | 1" | PLASTIC-BSP | 577 | 145 | 130 |

HOUSINGS WITH PLASTIC NPT THREADS

| CODE | MODEL | SUITABLE CARTRIDGE | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|---------------------------------|--------------------|--------|-------------|---------------|-----|-----|
| | | | | | A | B | C |
| SA107T513 | MEDIUM PLUS 3P AFP NPT SX SANIC | 5" | 3/4" | PLASTIC-NPT | 191 | 133 | 130 |
| SA107T813 | MEDIUM PLUS 3P BFP NPT SX SANIC | 5" | 1" | PLASTIC-NPT | 197 | 145 | 130 |
| SA109T513 | JUNIOR PLUS 3P AFP NPT SX SANIC | 7" | 3/4" | PLASTIC-NPT | 241 | 133 | 130 |
| SA109T813 | JUNIOR PLUS 3P BFP NPT SX SANIC | 7" | 1" | PLASTIC-NPT | 247 | 145 | 130 |
| SA111T521 | SENIOR PLUS 3P AFP NPT SX SANIC | 10" | 3/4" | PLASTIC-NPT | 315 | 133 | 130 |
| SA111T621 | SENIOR PLUS 3P BFP NPT SX SANIC | 10" | 1" | PLASTIC-NPT | 321 | 145 | 130 |
| SA115T513 | MASTER PLUS 3P AFP NPT SX SANIC | 20" | 3/4" | PLASTIC-NPT | 571 | 133 | 130 |
| SA115T813 | MASTER PLUS 3P BFP NPT SX SANIC | 20" | 1" | PLASTIC-NPT | 577 | 145 | 130 |